



EcoBond WB 07

Product Description

EcoBond WB 07 is a water-based, environmentally friendly solution designed to stabilize particulate landscaping materials such as stones, gravel, and bark. It prevents disintegration, reduces water absorption, inhibits weed growth, and enhances the vibrancy and color of decorative surfaces.

Product uses:

- Landscaping projects (gardens, parks, decorative pathways).
- Gravel and stone walkways.
- Bark and mulch areas.
- Decorative outdoor surfaces requiring stabilization.

Properties

- Eco-Friendly: Water-based, non-toxic formulation.
- Stabilization: Prevents scattering and deterioration of aggregates.
- Moisture Control: Reduces water absorption.
- Weed Resistance: Limits growth of weeds underneath.
- Aesthetic Enhancement: Maintains vibrant and colorful appearance.

TECHNICAL PROPERTIES

<i>Appearance/Color</i>	Milky liquid
<i>Density:</i>	1,00 ± 0,05
<i>Consumption:</i>	Approx. 3–5 m ² /L depending on substrate
<i>Application temperature (°C) :</i>	Apply Between +8°C and +30°C
<i>Drying Time (20 °C) :</i>	Touching Time : 3-5 hours/ Hard Drying Time : 36 hours
<i>Recoating Time (20°C) :</i>	4-6 hours.

Application Details

Application method: spray pump applicator or any spraying equipment
Thinner: The product is ready to use (**DO NOT THIN**)

Notes on Application / Limitations

The area must be free from rain and frost for a minimum of 72 hours after the application.

Application area should be completely dry and free from water.

The application surface can be opened to traffic after 3 days.

The product is not suitable for vehicles moves

The product may irritate the skin. Wear protective gloves, eye protection or face protection. Protective cream can also be applied to the hands before starting work.

In case of contact with eyes rinse cautiously with warm water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After the application, it hardens immediately. Hands and skin should be washed thoroughly in hot soapy water.

Clean tools and equipment with clean water immediately after use. Once hardened, product can only be removed mechanically.

Technical Data Sheet



Cleaning:

Clean all equipment and tools with water immediately after use.

Shelf life & Storage:

12 months from date of production if stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5°C and +30°C.

Safety:

For information and precautions on the safe handling, transportation storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notice:

The information presented herein is given in good faith but without warranty. It's based on our experience, indicates our laboratory work results and does not necessarily indicate final product performance. We cannot be held liable for the results obtained with our products and for any loss or accident that may result from its use. Our suggestions don't release you from the obligation to check their validity and to test our products for both your process and end use application. All our products are sold in accordance with our General Conditions of Sale. We don't make any warranty, express or implied, including but not limited to the merchant ability and fitness for a particular purpose.