



EpoGyard

Product Description

EpoGuard is a professional-grade epoxy floor cleaner designed to deliver powerful cleaning performance in demanding industrial and commercial environments. It effortlessly eliminates accumulated oils, dirt, tire scuffs, and heavy residues without attacking or dulling the epoxy coating, restoring a clean, vibrant, and polished finish.

Product uses:

It can be safely used on almost all surfaces, such as:

Epoxy, polyurethane, concrete, asphalt, bitumen, ceramic, marble, mosaic, stone, brick, plastic, Formica, laminate, glass, porcelain, rubber surfaces, metal surfaces, and stainless steel.

It does not damage the surface structure and does not cause dulling or discoloration.

Areas of Use:

- Factories with epoxy flooring
- Parking lots and warehouse areas
- Production lines and industrial facilities
- Technical areas in shopping malls
- Floors in food production facilities (non-contact zones)
- Workshops and logistics centers
- Areas where tarpaulins and water-based inks are cleaned

Properties

It is a high-performance surface cleaning solution developed specifically to ensure professional cleaning for floor scrubber-dryers, industrial washers, and epoxy floors subject to heavy traffic.

Thanks to its next-generation formula, it easily removes heavy grease and dirt from the surface without generating excessive foam, restoring the floor to its original, like-new shine.

Acts instantly on industrial oils, grease, heavy grime, and surface deposits.

Possesses strong dissolving power against water-based inks, industrial stains, and stubborn production-line soils.

Its low-foam formula ensures maximum efficiency and minimal maintenance requirements for floor cleaning machines.

Compatible with all types of professional cleaning equipment:

Floor cleaning machines Pressure washers

Steam cleaners

Spray systems

Wiping, brushing, and immersion applications

Can be used with hot or cold water.

Performance Benefits

- High solvency for oil, grease, and stubborn dirt
- Special formula that leaves no surface residue
- Fast and effective results
- Economical use – high efficiency over large areas
- Ideal for industrial operations, factories, and facilities with epoxy flooring



Application Details

- Depending on the required cleaning intensity, it can be applied directly or—thanks to its concentrated formula—diluted with water at ratios ranging from 1:5 to 1:30 for manual cleaning applications.
- For applications using automatic floor cleaning machines, the product should be diluted with water at ratios between 1:20 and 1:50. If there is heavy oiliness, dirt accumulation, or residue on the surface, the application may be repeated multiple times at 10-minute intervals.
- Rinsing the surface thoroughly with water after application is recommended, particularly in food production areas and on sensitive flooring.

PRECAUTIONS

- Read the instructions for use carefully before using the product.
- Do not use for cleaning hands, face, the body, or food items.
- In case of contact with eyes or skin, rinse immediately with plenty of water.
- Keep out of reach of children.
- Store the product in its original sealed packaging at room temperature, away from direct sunlight.
- Wear protective gloves during application; wear protective eyewear to guard against splashing.
- Avoid inhaling the product and prevent contact with eyes and skin.
- Good ventilation of the area is recommended during intensive application.

Shelf life & Storage:

12 months from date of production if stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5°C and +30°C.

Safety:

For information and precautions on the safe handling, transportation storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notice:

The information presented herein is given in good faith but without warranty. It's based on our experience, indicates our laboratory work results and does not necessarily indicate final product performance. We cannot be held liable for the results obtained with our products and for any loss or accident that may result from its use. Our suggestions don't release you from the obligation to check their validity and to test our products for both your process and end use application. All our products are sold in accordance with our General Conditions of Sale. We don't make any warranty, express or implied, including but not limited to the merchant ability and fitness for a particular purpose.